

Will not swell gaskets!
BLUE MONSTER®

LUBE-JOB

Pipe Joint Lubricant



For assembly of push-on pipe joints with natural rubber, synthetic rubber or plastic gaskets

Blue Monster® LUBE-JOB effectively lubricates pipe joints and gaskets for safe and efficient assembly of all types of pipelines, especially potable water systems.

LUBE-JOB is formulated from a biodegradable blend of lubricity enhancers and soaps creating a unique lubricant that flows into cavities when mating abutting pipes, effectively sealing joints. It's soft, creamy formula spreads on easily to give superior lubrication, performing well in extreme temperatures, whether hot or cold.

LUBE-JOB will not swell gaskets. It's petroleum and phosphate free – a special blend of raw materials common in the lubricant and soap industries. LUBE-JOB efficiently dissipates and will not leave a residue when flushed in accordance with recommended AWWA procedures. It will not irritate the skin, is non-toxic, and cleans up easily using warm water and soap.

Blue Monster® LUBE-JOB is certified to meet NSF/ANSI Standard 61 for potable water pipelines. NSF's use of strict analytical standards and formulation consistency assures production of a safe lubricant for water pipe joining requirements. In addition, LUBE-JOB is FBC System Compatible.

For Material Safety Data Sheets, contact Mill-Rose or download directly from the Mill-Rose Clean-Fit website.

FEATURES / BENEFITS

- Water dispersible
- Can be applied from -10° to 150°F
- Soft, creamy compound
- Meets NSF Standard 61-G
- Will not support bacteria
- Contains no petroleum
- Slow rate of solubility
- Non-toxic and Biodegradable
- FBC™ System compatible
- NSF approved • Low VOC

Compatible Synthetic Rubbers

- Butyl Rubber (IIR)
- Ethylene Propylene Diene Monomer (EPDM)
- Fluoroelastomers (FKM)/ Viton
- Polychloroprene (CR)/ Neoprene
- Silicone Rubber (SiR)
- Styrene Butadiene Rubber (SBR)

Technical Data

Form: Creamy Paste
 Color: Off-white
 Odor: Bland
 pH (5% in water) = Approx. 9.0
 Bulk Density: Approx. 9.3 lbs./gallon
 Maximum Penetration: 360 @ 77°F

Cat #	Size	Case Pack	Weight
71060	2 lbs. (.91kg)	12	24 lbs. (10.88 kg)



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan®, and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.



M/R
MILL-ROSE
Clean-Fit Products

7310 Corporate Blvd., Mentor, OH 44060

Orders 800.321.3598 or fax 440.255.1072 | BlueMonsterProducts.com | info@CleanFit.com